

Simple

Simple to use, simple to operate, install, and simple to operate, and simple to maintain.

Smart

Smart adjustment

Chlorine output is adjustable from 20% to 100% by simply pressing two buttons, satisfying different needs for different pools

Smart cleaning

Self-cleaning function by reversing the polarity automatically, which prevents calcium from accumulating and therefore prolongs the cell's lifetime

Smart alarm

Fault auto alarm with error code, which is easy to find corresponding solutions.

Smart protection

When the water temperature is too high or too low, the chlorinator will automatically stop running, in order to protect the unit and prolong the cell's life. The integrated sensors in the cell also ensure that water flow is adequate for safe chlorine generation

Smart memory system

Each time the chlorinator restarts, it can automatically initiate the last work status, with this smart memory function

Safe

Safe disinfection, safe water quality, and safe working voltage

Model	Size (mm)	Working Voltage (V)	Working Current (A)	Max Chlorine Output (g/h)	Dia. of Water Inlet and Outlet	Max Pool Volume (m ³)
EC 8	387x122x152	DC 24	4	8	1.5"/50mm	35
EC 12	387x122x152	DC 24	4	12	1.5"/50mm	50
EC 16	387x122x152	DC 24	4	16	1.5"/50mm	68
EC 20	387x122x152	DC 24	4	20	1.5"/50mm	85

Note: * In practice, the local pool standards and professional habits should be considered, and the adjusting allowance of 20-30% should be reserved.
* For outdoor pool, cyanuric acid (stabilizer) should be added to pool water, the ideal range for cyanuric acid is 25-50ppm when used.

